


MS21078 two lug anchor nuts. Cadmium-plated steel. Nylon locking insert. For blind mounted applications.

Part No.	Equivalent No.	Thread Size
MS21078-06	NAS1023N06	6-32
MS21078-08	NAS1023N08	8-32
MS21078-3	NAS1023N3	10-32
MS21078-4	NAS1023N4	1/4-28
MS21078-5	NAS1023N5	1/4-24




MS21080 one lug anchor nuts. Cadmium-plated steel. Nylon locking insert. Use where edge distance and space limitations do not permit use of two-lug or corner anchor nut.

Part No.	Equivalent No.	Thread Size
MS21080-06	NAS1025N06	6-32
MS21080-08	NAS1025N08	8-32
MS21080-3	NAS1025N3	10-32
MS21080-4	NAS1025N4	1/4-28



MS21081 corner anchor nuts. Cadmium-plated steel. Nylon locking insert. Use where space limitations do not permit an in-line arrangement of rivet holes.

Part No.	Equivalent No.	Thread Size
MS21081-06	NAS1027N06	6-32
MS21081-08	NAS1027N08	8-32
MS21081-3	NAS1027N3	10-32



MS21069 two lug thin anchor nuts. Heat-treated, cadmium-plated steel with dry film lubricant applied. High temp. Particularly suited for use in blind clearance areas.

Part No.	Equivalent No.	Thread Size
MS21069-04	NAS697A04	4-32
MS21069-06	NAS697A06	6-32
MS21069-08	NAS697A08	8-32
MS21069L3	NAS697A3	10-32
MS21069L4	NAS697A4	1/4-28



MS21059 two lug floating anchor nuts. Heat-treated, cadmium-plated steel with dry film lubricant applied. High temp. Counterbore in base area of nut eliminates shimming to prevent bottoming on the imperfect thread. Use to allow engagement of thread in cases of bolt hole misalignments.

Part No.	Equivalent No.	Thread Size
MS21059L06	NAS686AD6	6-32
MS21059L08	NAS686AD8	8-32
MS21059L3	NAS686AD3	10-32
MS21059L4	NAS686AD4	1/4-28



NAS679 low height hex nuts. Internal wrenching. Heat-treated, cadmium-plated steel with dry film lubricant applied. High temp.

Part No.	Thread Size
NAS679-A06W	.1380-32
NAS679-A08W	.1640-32
NAS679-A3W	.1900-32
NAS679-A4W	.2500-28
NAS679-A5W	.3125-24
NAS679-A6W	.3750-24
NAS679-A7W	.4375-20

