

Swageable terminals. Made of corrosion-resistant steel. When properly swaged to the cable, these terminals will maintain the minimum rated breaking strength of that cable (see Loos control cable for ratings, pp. 57–58).

Part No.	Cable Dia.	Hole Size	Description
MS20663C-2	1/16"	.073"	Ball and double shank
MS20663C-3	3/32"	.104"	Ball and double shank
MS20663C-4	1/8"	.139"	Ball and double shank
MS20664C-2	1/16"	.073"	Ball and single shank
MS20664C-3	3/32"	.104"	Ball and single shank
MS20664C-4	1/8"	.139"	Ball and single shank
MS20664C-5	5/32"	.169"	Ball and single shank
MS20664C-6	3/16"	.210"	Ball and single shank
MS20667C-2	1/16"	.190"	Fork end
MS20667C-3	3/32"	.190"	Fork end
MS20667C-4	1/8"	.190"	Fork end
MS20667C-5	5/32"	.250"	Fork end
MS20667C-6	3/16"	.313"	Fork end
MS20668C-2	1/16"	.190"	Eye end
MS20668C-3	3/32"	.190"	Eye end
MS20668C-4	1/8"	.190"	Eye end
MS20668C-5	5/32"	.250"	Eye end
MS20668C-6	3/16"	.313"	Eye end

RH Thread Part No.	LH Thread Part No.	Size & Thread	Cable Dia.	Description
MS21259-2RH	MS21259-2LH	6-40	1/16"	Terminal end
MS21259-3RH	MS21259-3LH	10-32	3/32"	Terminal end
MS21259-4RH	MS21259-4LH	1/4-28	1/8"	Terminal end
MS21259-5RH	MS21259-5LH	1/4-28	5/32"	Terminal end
MS21259-6RH	MS21259-6LH	5/16-24	3/16"	Terminal end
MS21259-7RH	MS21259-7LH	3/8-24	7/32"	Terminal end
MS21259-8RH	MS21259-8LH	3/8-24	1/4"	Terminal end
MS21259-9RH	MS21259-9LH	7/16-20	9/32"	Terminal end
MS21260L2RH	MS21260L2LH	6-40	1/16"	Terminal end
MS21260S2RH	MS21260S2LH	6-40	1/16"	Terminal end
MS21260L3RH	MS21260L3LH	10-32	3/32"	Terminal end
MS21260S3RH	MS21260S3LH	10-32	3/32"	Terminal end
MS21260L4RH	MS21260L4LH	1/4-28	1/8"	Terminal end
MS21260S4RH	MS21260S4LH	1/4-28	1/8"	Terminal end

Pulleys. MEETS MIL-DTL-7034.

Part No.	Old No.	O.D.	Description
MS20219-2	AN219-2	1 3/4"	Secondary control aircraft
MS20220-1	AN220-1	1 3/4"	Flight control pulley
MS20220-2	AN220-2	3"	Flight control pulley
MS20220-3	AN220-3	4 1/4"	Flight control pulley
MS20220-4	AN220-4	5 1/2"	Flight control pulley
MS24566-1B	AN210-1B	1 1/4"	Anti-friction bearing pulley
MS24566-2B	AN210-2B	2 1/2"	Anti-friction bearing pulley
MS24566-3B	AN210-3B	2"	Anti-friction bearing pulley
MS24566-4B	AN210-4B	3 1/2"	Anti-friction bearing pulley
MS24566-5B	AN210-5B	5"	Anti-friction bearing pulley

Cable shackles. AN115 shackles are listed as cadmium-plated steel. MS20115 shackles are corrosion-resistant shackles.


Part No.	Dimensions (D x F x G)	Used with Thimble	Used with Clevis Pin
AN115-8	1/2" x 1/4" x .109"	AN100-3	MS20392-2-9
AN115-16	1/2" x 3/8" x .150"	AN100-4	MS20392-2-11
AN115-21	5/8" x 3/8" x .150"	AN100-4	MS20392-2-11
AN115-32	5/8" x 7/8" x .203"	AN100-5	MS20392-3-15
AN115-46	3/4" x 1 1/2" x .203"	AN100-6	MS20392-4-17
MS20115-3	.190" x .254" x .108"	AN100-4	MS20392-2-11
MS20115-4	.190" x .383" x .195"	AN100-4	MS20392-2-11
MS20115-5	.250" x .406" x .202"	AN100-5	MS20392-3-15




MS20663C



MS20664C



MS20667



MS20668



MS21259



MS21260



R21-025-11

